



Tretford & Sahara Carpet Cleaning Instructions

TRETFORD

Maintenance on Walls

- ❖ To remove dust or fluff build-up, use a whisk broom or other medium-bristle brush to brush briskly but lightly in direction of ribs.
- ❖ Periodically vacuum surface in both directions using upholstery cleaning attachment with upright or canister vacuum cleaner.
- ❖ Pay particular attention to surfaces directly in line with heating/air conditioning vents, as these areas may require more frequent brushing and vacuuming.
- ❖ Remove spots and stains with any reputable commercial dry cleaning solvent. Apply solvent to area and BLOT (never rub) with clean absorbent cloth or paper towel.

Maintenance on Floors

- ❖ Tretford should be vacuumed daily with a pile-agitation vacuum cleaner. If the regular vacuum system relies on suction only, it is essential that a vacuum cleaner with pile-agitation be used.
- ❖ Spills should be blotted, not rubbed.
- ❖ If stain appears when dry, apply dry cleaning solvent and blot dry.
- ❖ Periodically, Tretford should be professionally and steam cleaned. Wet rotary shampooing is not recommended.
- ❖ Damaged or permanently stained areas may be cut out and neatly replaced with new patches.

SAHARA

Maintenance on Walls

- ❖ To remove dust or fluff build-up, use a corn broom or other medium-bristle brush to brush briskly but lightly in direction of ribs.
- ❖ Periodically vacuum surface in both directions using a handheld brush vacuum such as a Dirt Devil.
- ❖ Pay particular attention to surfaces directly in line with heating/air conditioning vents, as these areas may require more frequent brushing and vacuuming.
- ❖ Remove spots and stains with any reputable carpet stain remover such as Carpet-Aid, following manufacturer instructions.

Maintenance on Floors

- ❖ Sahara should be vacuumed daily. If the regular vacuum system relies on suction only, it is essential that a vacuum cleaner with pile-agitation be used.
- ❖ Remove spots and stains with any reputable carpet stain remover such as Carpet-Aid, following manufacturer instructions.
- ❖ Sahara can be cleaned with extraction method or rotary method.